

In the following, a survey of the four reports on screen will be given:

STOPPED	MONITOR	Picture name	15K 25/03/92 12:10 UTC
---------	---------	--------------	------------------------

Hold	Status	Sensor no.										
		1	2	3	4	5	6	7	8	9		
1A	I__ L_OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
1B	_D_ ON	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
1C	_D_ ON	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
2B	__C OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
2C	__C OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
2D	__C OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
3B	___ ON	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
3C	I__ OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
3D	I__ OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
4B	_D_ OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
4C	_D_ OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			
4D	_D_ OFF	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9	-99.9			

<u>H</u> old	<u>M</u> achinery	<u>A</u> larm-System	<u>C</u> ommon	<u>S</u> ystem
--------------	-------------------	----------------------	----------------	----------------

Fig. 2.2 The USDA report page 1.

Status refers to the following alarm suppressions:

- I = Inhibit
- D = Defrost
- A = Cooling Down

A '\*' located in front of a value in the printout indicates that an alarm condition exists for this particular sensor.