## C.N.P Freire Vigo Hull No. 392-393-394 RCM - Requirement specification.

In the following, a survey of the four reports on screen will be given:

STOPPED	MONITOR	Picture name	15K	25/03/92	12:10	UTC					
			1								

Hold	Stai	tus	1	2	Sens 3	sor no.	5	6	7	8	9
1A 1B 1C	I I D	L_OFF ON ON	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9			·
2B 2C 2D	c c	OFF OFF OFF	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9			
3B 3C 3D	I	ON OFF OFF	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9			
4B 4C 4D	_D_ _D_ _D_	OFF OFF OFF	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9	-99.9 -99.9 -99.9			

<u>H</u> old	<u>M</u> achinery	<u>A</u> larm-System	<pre>Common</pre>	<u>S</u> ystem					
1									

Fig. 2.2 The USDA report page 1.

Status refers to the following alarm suppressions:

I = Inhibit

D = Defrost

A = Cooling Down

A '\*' located in front of a value in the printout indicates that an alarm condition exists for this particular sensor.